

Marked Up Specification

This application claims the benefit, under 35 U.S.C. § 365 of International Application PCT/EP03/50319, filed July 18, 2003, which was published in accordance with PCT Article 21(2) on February 5, 2004 in English and which claims the benefit of French patent application No. 0209361, filed July 24, 2002.

Technical field of the invention

[0001] The invention relates to a method of distributing encrypted portions of an audiovisual ~~programme~~ program to user terminals, in particular television receiver decoders, in which method the successive portions of the ~~programme~~ program are encrypted with the aid of different keys before being distributed to the user terminals.

Background of the invention

[0002] In the present patent application, the expression "audiovisual ~~programme~~ program" designates any ~~programme~~ program, possibly audio, video or both audio and video. Such a ~~programme~~ program may in particular consist of a multimedia ~~programme~~ program of MPEG 4 type which may contain for example several video and/or audio sequences, three-dimensional data, two-dimensional graphs and/or associated animation scripts.

[0003] A method of distributing encrypted portions is known from patent document EP-1075108. In this method, one or more seed values are communicated selectively to the user terminals so that they can locally regenerate a limited set of decryption keys making it possible to decrypt a corresponding limited number of encrypted portions of the ~~programme~~ program. The communication of the seed values forms the subject of a billing to the user, the amount of which may vary as a function of the extent of the decryption. The billing may for example be on a per session or per subscription basis. A per subscription billing system proves to be complicated to set in place at the level of an audiovisual ~~centre~~ center which provides the encrypted ~~programme~~ program. Moreover, per session billing gives rise to an overall increase in the cost to the user of using the audiovisual service in the case where he profits from only a fraction of the ~~programme~~ program.

[0004] Furthermore, patent U.S. Pat. No. 4,916,737 discloses a technique in which scrambled video and/or audio portions are broadcast and are descrambled by means of a receiver decoder box. Moreover, a telephone modem linked with this box is periodically connected to a central computer of an operator, so as to receive a temporary identification code valid for the next period. This code is transmitted by the central computer only after recognition of a serial number specific to the relevant box. The periodicity of transmission

of the new code is for example monthly and the connection lasts for only a few seconds, so that the telephone line need only be tied up for a very short duration and frequency.

[0005] This technique is suitable for an overall subscription for a given period and requires complicated management of the subscriptions. It does not allow billing adapted in a simple manner to the ~~programme~~ program actually viewed by a user.

[0006] U.S. Pat. No. 4,890,322 describes a service for distributing announcement messages which is used to control TV signals, ~~programme~~ program by ~~programme~~ program. The enciphered signals sent are deciphered at the level of each subscriber by a deciphering unit, by virtue of the use of a nondedicated telephone service line. With each order from a subscriber, the deciphering unit automatically transmits the subscriber's request to the distribution service via the telephone service line, and receives in return, via this same line, coded key information necessary for deciphering the desired ~~programme~~ program. The key information obtained is used for the duration of the ~~programme~~ program ordered. By way of example, the description mentions a deciphering key transmitted to the subscriber in the form of a message repeated for three seconds, this key being in the form of a number consisting of coded numerical values which may be used to fix the coefficients of a signal filter.

[0007] This method makes billing per ~~programme~~ program possible without, however, allowing finer billing (for example to view a given part of a broadcast), while requiring complicated management of billing.

[0008] To improve the fineness of control on the part of users, provision may be made for the independent transmission of parts of ~~programme~~ program, each being able to form the subject of a specific request. Thus, depending on the availability thereof, a user may decide to view a first part of a film on a first evening, then a second part on another evening. However, such a solution yet further complicates the management of transmission and billing, all the more so the more elaborate the offerings--for example if they allow a viewer to choose the duration of each of the parts.

Summary of the invention

[0009] The invention proposes a method of distributing encrypted portions of an audio and/or video ~~programme~~ program which permits simpler and finer billing of the service while being able to offer security against piracy.

[0010] The method according to the invention is characterized in that it consists, on initiation, from a user terminal, of a telephone communication with a call ~~centre~~ center, in transmitting in sequence from this call ~~centre~~ center and during the telephone communication the keys to the user terminal, doing so in a

manner synchronized with the distribution of the successive encrypted portions of the ~~programme~~ program. Of course, the distribution of the successive encrypted portions of the ~~programme~~ program may be carried out by broadcasting over cable, by satellite or over the airwaves. The call ~~centre~~ center is preferably a ~~centre~~ center for receiving telephone calls of a telephone operator in which means exist for measuring, with each call of a user terminal, the time of the telephone communication therewith so that, on the basis of this information, an appropriate bill can be generated easily in respect of the corresponding user.

[0011] It is understood that, so long as the telephone communication is set up between the call ~~centre~~ center and a user terminal, a decryption of the current portions of the ~~programme~~ program is made possible locally in the user terminal. However, on completion of the telephone communication, the current encrypted portions of the ~~programme~~ program are no longer decrypted since the keys no longer arrive at the user terminal. The duration of plaintext reception of the ~~programme~~ program therefore corresponds overall to the duration of the telephone communication so that the user pays only in respect of the actual duration for which he profits from the audiovisual service.

[0012] The method of the invention contrasts surprisingly with the state of the art, in which one strives to reduce as far as possible the duration of telephone communication required to obtain the decryption data. Specifically, the method of the invention relies on the contrary on the continuity of the telephone communication throughout the distribution of the encrypted ~~programme~~ program. These characteristics permit not only a broadcasting of audiovisual ~~programme~~ program for a duration decided exactly by the user in real time, but also a payment for this service directly by telephone billing.

[0013] The method according to the invention also advantageously exhibits the following features:

[0014] the telephone communication utilizes an Internet protocol;

[0015] synchronization time codes are transmitted in correspondence with the successive keys during the telephone communication.

[0016] The invention extends to a decoder for receiver of audio and/or video ~~programme~~ program, in which successive portions of a ~~programme~~ program are decrypted with the aid of a succession of different keys, characterized in that it is designed to be connected up, by way of a telephone communication interface, to a call ~~centre~~ center and to recover the successive keys in sequence during the communication with the call ~~centre~~ center and to do so in a manner synchronized with the decryption of the successive portions of the ~~programme~~ program.

[0017] According to preferred features of this decoder:

[0018] the telephone communication interface is a telephone modem in particular of the ADSL modem type which utilizes an Internet protocol.

[0019] The invention extends also to a decryption routine adapted for loading into the memory of a decoder for receiver of audio and/or video ~~programme~~ program having a telephone communication interface.

Brief description of the drawings

[0020] The method, the decoder and the routine according to the invention are described hereinbelow in greater detail and illustrated through the single FIGURE which diagrammatically represents a system for distributing pay video and/or audio ~~programme~~ program.

Detailed description of the preferred embodiments

[0021] Represented in the FIGURE by way of nonlimiting example are just two user terminals T1, T2 each comprising a receiver R1, R2 of audio and/or video ~~programme~~ program, a decoder D1, D2 as well as a communication interface M1, M2 of the telephone modem type.

[0022] The receivers R1, R2 are here television receivers. The communication interfaces M1, M2 could form an integral part respectively of the decoders D1, D2 which may be decoders of the "set top box" type.

[0023] Each decoder D1, D2 is able to receive on an input channel C1, C2 successive encrypted portions of an audio and/or video ~~programme~~ program. These ~~programme~~ program portions are digital frames.

[0024] The encrypted portions of the ~~programme~~ program are distributed here to the user terminals T1, T2 by the RF channel 1 from a broadcasting antenna 2 which is linked to an audiovisual ~~centre~~ center 3 which provides the ~~programme~~ program. In the audiovisual ~~centre~~ center 3, the successive portions of the ~~programme~~ program are encrypted using a succession of different encryption keys so as to limit the possibilities of piracy. The encryption key used to encrypt the successive portions of the ~~programme~~ program is changed at the end of each sequence of n successive portions, the value of n being adjusted so as to have a different encryption key for example every 30 seconds of showing of the ~~programme~~ program on the screen.

[0025] The use of time codes in digital audiovisual streams is known: DTS (Decoding Time Stamp), PTS (Presentation Time Stamp) and PCR (~~programme~~ program Clock Reference) in MPEG2-TS streams. These time codes are inserted into each encrypted portion of the ~~programme~~ program and make it possible to synchronize the decoder D1, D2 with the clock of the transmitter 3 of the audiovisual ~~programme~~ program.

[0026] According to one aspect of the invention, time codes of the DTS type are associated during encryption in the audiovisual ~~centre~~ center 3 with the various encryption keys. This association will serve during the decryption of the portions of the ~~programme~~ program in a decoder to prevent the decryption of a portion of the ~~programme~~ program if the time code associated with the decryption key provided for this portion of the ~~programme~~ program is not synchronized with the time code DTS recovered in this portion of the ~~programme~~ program.

[0027] The reference 4 in the FIGURE indicates a telephone call ~~centre~~ center which receives in sequence from the audiovisual ~~centre~~ center 3 the succession of encryption keys, doing so in a manner synchronized with the broadcasting of the successive portions of the ~~programme~~ program by the antenna 2 and hence with the receiving in sequence of these portions of the ~~programme~~ program by the user terminals T1, T2.

[0028] In order for the ~~programme~~ program to be shown as plaintext at the level of the receiver R1, R2 of a user terminal T1, T2, the user operates his decoder D1, D2, decoder to initiate a telephone communication with the call ~~centre~~ center 4 by way of a communication interface M1, M2 of the modem type. The call number of the call ~~centre~~ center may be prerecorded in the decoder so as to make the opening of the telephone communication automatic. During the telephone communication, the decoder D1, D2 will be able to be identified by the call ~~centre~~ center 4 and, following identification, the call ~~centre~~ center 4 transmits in sequence via the telephone path to the user terminal T1, T2 the current successive keys serving for the decryption of the current portions of the ~~programme~~ program received in parallel by the decoder D1, D2. The transmission in sequence by the call ~~centre~~ center 4 of these keys each associated with a time code is done in a manner synchronized with the broadcasting of the portions of the ~~programme~~ program by the antenna 2. In the FIGURE, "x, y, z, . . ." represents the successive decryption keys and "t1, t2, t3, . . ." represents the time codes associated with the decryption keys.

[0029] In each decoder D1, D2, the decryption procedure is organized in such a way that the successive keys together with the associated time codes recovered by way of the communication interface M1, M2 are checked by comparison with the DTS time codes located in the encrypted portions of the ~~programme~~ program received by the decoder. Stated otherwise, a key associated with a time code t1 will be rejected if the ~~programme~~ program portion received in parallel with the recovery of this key contains a DTS time code prior to t1. This ~~programme~~ program portion will therefore not be decrypted in the decoder.

[0030] In practice, the successive keys together with the respective time codes are recovered in the user terminal with a slight lead with respect to the corresponding portions of ~~programme~~ program and a temporary storage of the

keys must therefore be organized in the decoder so as to allow the decryption during the reception of the current portion of ~~programme~~ program. When a key together with a time code t1 is recovered by the decoder, it is stored in the temporary memory of the decoder if the DTS time code of the current portion of the ~~programme~~ program is prior to the time code t1 associated with the key. In the converse case, the key is rejected and is therefore not recorded in the temporary memory of the decoder. During the decryption of a current portion of the ~~programme~~ program, the key necessary for this

[0031] The decryption procedure hereinabove may be implemented by a routine loaded into memory in a conventional programmable decoder equipped with a telephone communication interface.

[0032] The communication interface will preferably be a modem of the ADSL type which will advantageously utilize an Internet communication protocol to allow multiple communications on the same telephone line.